

UNMATCHED  
QUALITY  
**UNRIVALED**  
PERFORMANCE



**GHAURI TYRE & TUBE (PVT) LTD.**

HEAD OFFICE & FACTORY  
146-M, Industrial Area Kot Lakhpat, Lahore Pakistan.  
TEL: 042 111 488 488

[www.ghaurityres.com](http://www.ghaurityres.com) [f ghaurityres](https://www.facebook.com/ghaurityres) [i ghaurityres.official](https://www.instagram.com/ghaurityres) [y ghaurityres.official](https://www.youtube.com/ghaurityres)



**PRODUCT  
CATALOG**



**DELIVERING  
THE BEST  
EVERY TIME**

[www.ghaurityres.com](http://www.ghaurityres.com)





# PRESTIGE CAN ONLY BE EARNED



## ABOUT US

Established in 1998, Ghauri Tyres is among the pioneers of tire industry in Pakistan. Our unwavering commitment to quality and service delivery has ensured 100% customer satisfaction. Ghauri Tyres is hailed among the most trustworthy and credible tire brands in Pakistan.

We have grown many folds over time with an installed production capacity of 7 million tires and 9 million tubes per annum. We proudly serve two-wheel and three-wheel segments, manufacturing excellent tires and tubes for Motorcycles, Scooters, E-Bikes, Bicycles, Rickshaws, ULT and Wheel Barrow.

Our tires and tubes are highly sought after in the market owing to their durability, mileage, stability and tread designs.

Ghauri Tyres, with its global ambition, is exporting its products to more than 10 destinations in Asia. With a deep focus on development of superior products, we are now aiming to increase our global footprint by expanding our network to Africa, Europe and South America.

To our customers, we ensure excellent quality, cutting edge products and value for their money.



**GHAURI**  
TYRES

LEADING TO  
SUCCESS



**GHAURI**  
TYRES





## SPORTS

With a sporty twist to time tested block design, this profile provides uncompromised road grip and ride stability. Meticulously designed grooves provide excellent water dispersion capability to enhance rider safety on wet roads.

TYRE SIZE	PR	Weight/Volume	Sec width (mm)	Load / Speed Index	Max Pressure (PSI)
2.50-17R	6	1.950	85	45 L	41
2.50-18R	6	2.000	85	45 L	41
2.75-18 RTL	6	2.400	75	48 L	41
3.00-17R	6	2.700	80	50 L	41
3.00-18 RTL	6	2.800	80	52 L	41
90/90-18 RTL	6	3.300	90	51 L	35
100/90-18 RTL	6	4.500	101	62 L	41

## ZOOM

Especially designed for extra ordinary safety and road grip features, Zoom provides a blend of smooth ride, cornering ability and braking support. Excellent cornering ability provides agile riding experience.

TYRE SIZE	PR	Weight/Volume	Sec width (mm)	Load / Speed Index	Max Pressure (PSI)
2.50-17R	6	2.850	85	43 L	41
3.00-17R	6	2.800	80	50 L	41
90/90-18 RTL	6	3.150	90	62 L	41
100/90-18 RTL	6	4.150	101	62 L	41



## CLASSIC

A modern and sleek adaption of classic shoulder block design with a central rib, this profile uniquely blends fuel efficiency and superior road grip. Special diamond faced blocks on shoulders provide extra grip while cornering, enhancing safety and comfort.

TYRE SIZE	PR	Weight/Volume	Sec width (mm)	Load / Speed Index	Max Pressure (PSI)
2.75-17 RTL	6	2.300	75	45 L	41
2.75-18 RTL	6	2.400	75	48 L	41

## TRAIL SAFARI 4

Designed for strength and stability, this profile boasts wider teeth to maximize grip and stability for extreme off-roading.

TYRE SIZE	PR	Weight/Volume	Sec width (mm)	Load / Speed Index	Max Pressure (PSI)
3.00-18 RTL	6	2.800	80	52 L	41





## MOTORCYCLE TYRES



### CLASSIC

A modern and sleek adaption of classic shoulder block design with a central rib, this profile uniquely blends fuel efficiency and superior road grip. Special diamond lead blocks on shoulders provide extra grip while cornering, enhancing safety and comfort.

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)	Load / Speed Index	Max Pressure (PSI)
2.50-17R	6	1.850	85	43L	41
3.00-17R	6	2.700	80	58L	41

### LOGLIFE / CHAMPION

A unique and modern profile for the modern city streets. Long-life provides great stability, smoothness and ride comfort. Its increased surface area ensures sufficient road grip and safety.

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)	Load / Speed Index	Max Pressure (PSI)
2.50-17R	6	1.950	85	43L	41
3.00-17R	6	2.700	80	58L	41



### RIDER

Modern block design of Rider provides excellent surface contact area to enhance ride stability and road grip. Unique profile supports frequent braking on traffic packed city roads.

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)	Load / Speed Index	Max Pressure (PSI)
2.50-17R	6	2.050	85	43L	41



## MOTORCYCLE TYRES



### OLYMPIC

Bold block profile of Olympic provides enhanced stability and road grip with durability and long life of the

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)	Load / Speed Index	Max Pressure (PSI)
2.50-17R	6	2.050	85	43L	41

### KING

King is another multi block pattern providing stability, durability and road grip. Special compounding and unique tread design guarantees safer and smoother rides.

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)	Load / Speed Index	Max Pressure (PSI)
2.50-17R	6	2.050	85	43L	41



### EAGLE

Multi block profile of Eagle is designed for improved road grip and ride stability. Equally effective in dry and wet conditions, the unmatched braking ability of this profile ensures ride safety.

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)	Load / Speed Index	Max Pressure (PSI)
2.50-17R	6	2.050	85	43L	41
3.00-17R	6	2.800	80	58L	41



# MOTORCYCLE TYRES



## TIGER

Tiger is designed for additional support while braking and overall feel of superior road grip on the city streets. Enhanced cornering ability provides agility while navigating through bustling city traffic.

TYRE SIZE	PR	Weight/Tolerance	Sec-wth (mm)	Load / Speed Index	Max Pressure (PSI)
2.50-17R	6	1.908	65	43L	41
2.50-18R	6	2.230	65	45L	41
3.00-17R	6	2.700	80	50L	41

## CONTINENTAL

An adaptation of our trade mark Classic-2 pattern, Continental provides enhanced road grip and cornering ability.

TYRE SIZE	PR	Weight/Tolerance	Sec-wth (mm)	Load / Speed Index	Max Pressure (PSI)
2.50-17R	6	1.908	65	43L	41



## LONG LIFE

A Unique and modern profile for the modern city streets. Long-Life provides great stability smoothness and ride comfort. Its increased surface area ensures sufficient road grip and safety.

TYRE SIZE	PR	Weight/Tolerance	Sec-wth (mm)	Load / Speed Index	Max Pressure (PSI)
2.50-17R	6	1.908	65	43L	41
2.50-18R	6	2.230	65	45L	41



# MOTORCYCLE TYRES



## SUPER SONIC

This profile is famous for its durability, stability and all-weather application. The tire provides maximum mileage and strength while ensuring safety.

TYRE SIZE	PR	Weight/Tolerance	Sec-wth (mm)	Load / Speed Index	Max Pressure (PSI)
2.50-17R	6	1.908	65	43L	41
2.50-18R	6	2.230	65	45L	41
3.00-17R	6	2.700	80	50L	41

## GOLD

Crafted with an advanced rubber compound, this tire delivers exceptional road grip, enhanced safety, and superior rider comfort. Its robust tread design maximizes road contact, providing a smoother, more secure ride, perfect for those who demand both performance and reliability on every journey.

TYRE SIZE	PR	Weight/Tolerance	Sec-wth (mm)	Load / Speed Index	Max Pressure (PSI)
2.50-17R	6	2.068	65	43L	41



## ROTATIONAL

With a unique laser profile design around a central rib, Rotational provides a comfortable riding experience on city roads. Blocks on the shoulders provide added stability while cornering at high speed.

TYRE SIZE	PR	Weight/Tolerance	Sec-wth (mm)	Load / Speed Index	Max Pressure (PSI)
2.50-17R	6	1.956	65	43L	41
2.50-18R	6	2.260	65	45L	41
3.00-17R	6	2.730	80	50L	41



## MOTORCYCLE TYRES



### SPORTS PLUS

Designed for sporty looks and extra grip, this unique profile provides additional safety features for enthusiastic riders.

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)	Load / Speed Index	Max Pressure (PSI)
3.00-17 R	6	2.700	80	43L	41

### TRAIL SAFARI-1

Trail Safari's beautiful block design is specially designed to provide exceptional grip while off-roading. Multiple deep blocks cleave into the surface for extra ordinary stability on rough terrain.

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)	Load / Speed Index	Max Pressure (PSI)
2.50-17 R	6	1.900	65	43L	41
2.75-17 R	6	2.300	75	43L	41
2.75-48 R	6	2.400	75	43L	41
3.00-18 R	6	2.800	80	52 L	41



### TRAIL SAFARI-2

Trail Safari - 2 is a uniquely designed profile for mud and gravel applications during off-roading. Compartmentalized block design ensures extra stability during off-roading. Carefully spaced teeth ensure that mud or gravel don't get stuck in the tire.

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)	Load / Speed Index	Max Pressure (PSI)
2.50-18 R	6	2.250	65	43L	41



## MOTORCYCLE TYRES



### TRAIL SAFARI-3

With wider and more spacious block design, this profile provides flexibility and comfort on off-road tracks

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)	Load / Speed Index	Max Pressure (PSI)
3.00-17 R	6	2.700	80	50 L	41

### SPORTAGE

Sporty profile with enriched rubber compound, this tire is designed for enhanced road grip, safety and rider comfort. Bold block design improves road contact to ensure smoother and safer rides.

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)	Load / Speed Index	Max Pressure (PSI)
2.50-17 R	6	1.800	65	43L	41
2.50-18 R	6	2.150	65	46L	41
2.75-17 R TL	6	2.300	75	43L	41
2.75-48 R	6	2.400	75	46L	41
3.00-17 R	6	2.700	80	50 L	41



### CLASSIC-1

A modern and sleek adaptation of classic shoulder block design with a central rib, this profile uniquely blends fuel efficiency and superior road grip. Special diamond faced blocks on shoulders provide extra grip while cornering, enhancing safety and comfort.

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)	Load / Speed Index	Max Pressure (PSI)
2.25-17 F	6	1.630	61	38L	41
2.75-18 F TL	6	2.400	75	48L	41



## MOTORCYCLE TYRES



### SPORTS

Intended to be used in pair with Sports (S) series, this profile is crafted for enhanced road grip and sporty looks

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)	Load / Speed Index	Max Pressure (PSI)
2.25-17 F	6	1.630	80	38L	41
2.30-18 F	6	2.250	85	45L	41

### LONGLIFE

Designed for front wheel applications, this profile features cut blocks in the middle to increase road grip and braking ability without compromising smooth steering

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)	Load / Speed Index	Max Pressure (PSI)
2.25-17 F	6	1.630	81	38L	41
2.50-17 F	6	1.850	85	46L	41



### TIGER

Intended to be used in pair with Tiger (T) series, this profile provides enhanced cornering ability and steering agility resulting in smoother ride on city streets

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)	Load / Speed Index	Max Pressure (PSI)
2.25-17 F	6	1.630	80	38L	41



## MOTORCYCLE TYRES



### SUPER SONIC

A modern adaptation for front wheel application, this profile features continuous central ribs resulting in very smooth steering. Block pattern on shoulder improves grip while cornering.

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)	Load / Speed Index	Max Pressure (PSI)
2.25-17 F	6	1.630	81	38L	41
2.50-18 F	6	2.250	85	45L	41

### CLASSIC 2

Designed for city streets, this classic profile provides an amazing blend of comfort and ride stability.

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)	Load / Speed Index	Max Pressure (PSI)
2.50-18 F	6	2.250	85	45L	41





# RIDE WITH STYLE



SCOOTY  
TYRES



## SONIC

Designed to achieve superior road grip and rider safety without compromising smooth riding experience and fuel efficiency, this profile provides an excellent combination of a sleek design and safety features.

TYRE SIZE	PR	Weight/Tolerance	Sec. with (mm)	Load / Speed Index	Max Pressure (PSI)
3.00-18 TL	6	2.000	82	81 L	43

## THUNDER

This profile is particularly designed to provide road grip and ride stability. Big blocks of the prevent slipping and provide extra grip during braking. Special rubber compound provides durability and ensures safety.

TYRE SIZE	PR	Weight/Tolerance	Sec. with (mm)	Load / Speed Index	Max Pressure (PSI)
3.50-18 TL	6	2.400	84	59 L	40
90-90-12 TL	6	2.550	80	59 L	40



## STORM

This pattern is designed to ensure smooth riding experience. Laser grooves help disperse water in wet conditions. Additional grooves on the shoulders provide support during cornering.

TYRE SIZE	PR	Weight/Tolerance	Sec. with (mm)	Load / Speed Index	Max Pressure (PSI)
100-80-10 TL	6	2.800	88	81 L	43

**GHAURI**  
TYRES**SCOOTY**  
TYRES

## X-STREET

Designed to rule the city street this pattern provide excellent combination of grip and efficiency. Deep water channels ensure smooth water dispersion in wet conditions.

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)	Load / Speed Index	Max Pressure (PSI)
3.00-10 TL	6	2,000	82	48 L	40
3.50-10 TL	6	2,400	94	51 L	40
10.00-12 TL	6	2,750	98	58 L	40

## PRO-CITY

This profile achieves superior road grip while riding and braking. Special compound helps prevent slippage.

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)	Load / Speed Index	Max Pressure (PSI)
2.00-10 TL	6	2,000	82	48 L	40
3.50-10 TL	6	2,450	96	51 L	40
10.00-12 TL	6	2,750	98	58 L	40



## E-CITY

Designed on E-bike specifications with the strength to support rapid acceleration and deceleration. Diserts minimum load on the motor to increase efficiency.

TYRE SIZE	Weight/Tolerance
14X2.50 TL	1300
16X2.50 TL	1450

**GHAURI**  
TYRES



**BICYCLE  
TYRES**



**HEAVY DUTY-1**

TYRE SIZE Weight/Tolerance

2800 1/2 1090 ± 10



**HEAVY DUTY-2**

TYRE SIZE Weight/Tolerance

2800 1/2 1060 ± 10



**HEAVY DUTY-3**

TYRE SIZE Weight/Tolerance

2800 1/2 1060 ± 10



**HEAVY DUTY-4**

TYRE SIZE Weight/Tolerance

2800 1/2 1060 ± 10



**HEAVY DUTY-5**

TYRE SIZE Weight/Tolerance

2800 1/2 1090 ± 10



**HEAVY DUTY-6**

TYRE SIZE Weight/Tolerance

2800 1/2 1060 ± 10



**BICYCLE  
TYRES**



**HEAVY DUTY-7**

TYRE SIZE Weight/Tolerance

2800 1/2 1090 ± 10



**GOLD STONE**

TYRE SIZE Weight/Tolerance

2800 1/2 940 ± 10



**SUPERME**

TYRE SIZE Weight/Tolerance

2800 1/2 940 ± 10



**INDONESIA**

TYRE SIZE Weight/Tolerance

2800 1/2 1045 ± 5



**PRINCE**

TYRE SIZE Weight/Tolerance

2800 1/2 940 ± 10



**EAGLE**

TYRE SIZE Weight/Tolerance

2800 1/2 940 ± 10



**BICYCLE  
TYRES**



### K-2 CLASSIC

TYRE SIZE Weight/Tolerance

200T 1/2 940 ± 10



### IRANI LOADER

TYRE SIZE Weight/Tolerance

200T 1/2 1045 ± 5  
20X2.00 1040 ± 10  
290 3/8 790 ± 10  
240 3/8 725 ± 5



### LONG LIFE

TYRE SIZE Weight/Tolerance

200 1/2 940 ± 10  
25X1 3/8 790 ± 10  
24X1 3/8 725 ± 5  
20X1 3/8 628 ± 10



### RACER

TYRE SIZE Weight/Tolerance

270 1/4 800 ± 10



### ROCKY

TYRE SIZE Weight/Tolerance

25X2.1 1040 ± 10  
26X2.125/1.95 1040 ± 10



### SPEED

TYRE SIZE Weight/Tolerance

29X2.1 1040 ± 10



**BICYCLE  
TYRES**



### MTB/BMX-1

TYRE SIZE Weight/Tolerance

25X2.125 1040 ± 10  
26X1.95 1040 ± 10  
20X2.125 905 ± 5  
18X2.125 610 ± 10



### MTB/BMX-2

TYRE SIZE Weight/Tolerance

26X2.125 1040 ± 10  
20X2.125 905 ± 5



### MTB/BMX-3

TYRE SIZE Weight/Tolerance

26X2.125 1040 ± 10  
26X1.95 1040 ± 10  
20X2.125 905 ± 5



### MTB/BMX-4

TYRE SIZE Weight/Tolerance

26X2.125 1040 ± 10  
26X1.95 1040 ± 10  
20X2.125 905 ± 5  
20X1.85 905 ± 5



### MTB/BMX-5

TYRE SIZE Weight/Tolerance

20X2.125 1040 ± 10  
20X2.125 905 ± 5



### MTB/BMX-6

TYRE SIZE Weight/Tolerance

20X2.125 1040 ± 10  
20X2.125 905 ± 5  
20X1.85 905 ± 5



**BICYCLE  
TYRES**



### TRACTOR

TYRE SIZE Weight/Tolerance

26X2.25/1.95 1040 ± 10  
240X95 1040 ± 10



### TIGER

TYRE SIZE Weight/Tolerance

26X2.25/1.95 1040 ± 10



### LUCKY

TYRE SIZE Weight/Tolerance

26X2.25/1.95 1040 ± 10



### GRAVITY HD

TYRE SIZE Weight/Tolerance

26X2.25/1.95 1040 ± 10



### RIDER

TYRE SIZE Weight/Tolerance

26X2.25/1.95 1040 ± 10  
25X1.75 1040 ± 10  
240X95 1000 ± 10



### TIGER PLUS

TYRE SIZE Weight/Tolerance

26X2.25/1.95 1040 ± 10  
240X95 1040 ± 10



**BICYCLE  
TYRES**



### ARROW-1

TYRE SIZE Weight/Tolerance

26X2.25/1.95 1040 ± 10  
200X125 935 ± 5



### DOUBLE ARROW

TYRE SIZE Weight/Tolerance

28X2.125 950 ± 5



### SRS

TYRE SIZE Weight/Tolerance


23X2.125 905 ± 5  
16X1.075 588 ± 12



### OMEGA

TYRE SIZE Weight/Tolerance

28X2.125 935 ± 5  
19X2.125 810 ± 10  
16X1.075 588 ± 12



### TURBO

TYRE SIZE Weight/Tolerance

20X3.00 1230 ± 20  
16X3.00 1000 ± 20



**RICKSHAW  
TYRES**



## DISCOVERY

TYRE SIZE	PR	Weight/Tolerance	Sec-with (mm)	Load / Speed Index	Max Pressure (PSI)
4.00-8(1)TL	8	2.300	109	25K5	35PSI

## COMMANDO

TYRE SIZE	PR	Weight/Tolerance	Sec-with (mm)	Load / Speed Index	Max Pressure (PSI)
4.00-8(1)TL	8	2.500	109	25K6	35PSI



## SPORTS

TYRE SIZE	PR	Weight/Tolerance	Sec-with (mm)	Load / Speed Index	Max Pressure (PSI)
4.00-8(1)TL	8	2.300	109	25K5	35PSI



**RICKSHAW  
TYRES**



## SPORTS TRIANGLE

TYRE SIZE	PIR	Weight/Tolerance	Sec-with (mm)	Load / Speed Index	Max Pressure (PSI)
4.00-8 TT/TL	8	2.900	189	276G	35PSI

## SPORTS MRF

TYRE SIZE	PIR	Weight/Tolerance	Sec-with (mm)	Load / Speed Index	Max Pressure (PSI)
4.00-8 TT/TL	8	2.900	189	276G	35PSI



## OLYMPIC

TYRE SIZE	PIR	Weight/Tolerance	Sec-with (mm)	Load / Speed Index	Max Pressure (PSI)
4.00-8 TL	8	2.900	189	276G	35PSI





**TROLLEY  
TYRES**



## TRIANGLE

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)
400-6TT	1	2,400	80

## CHAMPION

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)
300-6TT	2	1,000	80



## TRACTOR

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)
350-6TT	4	1,700	92



**TROLLEY  
TYRES**



## LONG LIFE

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)
150-6TT	2	1,550	92

## SUPER

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)
150-6TT	2	1,550	92



## YAZD

TYRE SIZE	PR	Weight/Tolerance	Sec-width (mm)
150-6TT	4	1,700	92



## MC (BUTYL TUBES)

SR. NO#	SIZE	Application	Type	Flat Width (mm)	Nozzal Type
1	2.25/50-17	70 cc Front/Rear	Natural / Butyl Rubber	55	TR-4
2	2.50-17	70 cc Front/Rear	Natural / Butyl Rubber	72	TR-4
3	2.50-18	100 cc Front/Rear	Natural / Butyl Rubber	72	TR-4
4	3.00-17	125 cc Rear	Natural / Butyl Rubber	84	TR-4
5	3.00-18	125 cc Rear	Natural / Butyl Rubber	84	TR-4
6	90/90-16	150 cc Rear	Natural / Butyl Rubber	92	TR-4
7	100/90-16	150 cc Rear	Natural / Butyl Rubber	92	TR-4

## BC TUBES

SR. NO#	Etrio Size	Inch Size	Type	Nozzal Type	Flat Width (mm)	
					Natural	Butyl
1	40-635	28x1-1/2	Natural / Butyl Rubber	TR1 / VAR 29-32	43	43
2	32-630	27x1-1/4	Natural / Butyl Rubber	TR1 / VAR 28-33	34	34
3	57-599	26x1.75/1.25	Natural / Butyl Rubber	TR1 / VAR 28-34	56	43
4	50-559	26x1.75/1.25	Natural / Butyl Rubber	TR1 / VAR 29-35	56	43
5	57-507	24x2.125	Natural / Butyl Rubber	TR1 / VAR 28-36	56	43
6	57-406	20x2.125	Natural / Butyl Rubber	TR1 / VAR 28-37	56	43
7	47-305	16x1.75	Natural / Butyl Rubber	TR1 / VAR 28-38	56	43
8	37-590	26x1-3/8	Natural / Butyl Rubber	TR1 / VAR 29-39	43	43
9	37-540	24x1-3/8	Natural / Butyl Rubber	TR1 / VAR 28-40	43	-
10	37-451	20x1-3/8	Natural / Butyl Rubber	TR1 / VAR 28-41	43	-
11	76-406	20x3.00	Butyl Rubber	AV-48	-	-
12	76-305	16X3.00	Butyl Rubber	AV-48	-	-

## SCOOTER, RICKSHAW TUBES

SR. NO#	SIZE	Application
1	4.00-8	Rickshaw
2	135-10	Rickshaw

## NATURAL TUBES WHEEL BARROW

SR. NO#	SIZE	Application
1	3.00-8	Wheel Barrow
2	3.50-8	Wheel Barrow
3	3.50/4.00-8	Wheel Barrow

